



| Type/Order No | OBO01-12-8040-TD |
|--|---|
| Lamp type/assembly | Standing light |
| Size | H 1500 mm |
| Light source | LED |
| Colour temperature | 4000 K |
| Colour rendering index | CRI > 80 |
| Chromaticity tolerance (initial MacAdam) | 3 SDCM |
| Operating mode | Dimmable |
| Operation | On lamp |
| Ballast (number) | DALI converter (1), integrated in luminaire |
| Lamp shade | Polyester fleece |
| Base | Steel, white-aluminium, powder-coated |
| Power cable | Black, 3 x 0.75mm ² , L 3000 mm |
| Mains plug | Schuko plug type E+F |
| Light distribution | Diffuse |
| Total luminous flux | 8600 lm @ 4000 K |
| Power consumption | 64 W |
| Luminaire efficacy | 130 lm/W |
| LED service life | 50 000 h (L80/F10) |
| Mains voltage | 220-240V, 50Hz |
| Stand-by consumption | < 0.5W |
| Safety class | I |
| Protection type | IP 20 |
| Packaging units | 1 (1550 x 410 x 360 mm) |
| Weight | 15.0 kg |
| Guarantee | 36 months |

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com



reddot



≈39.79% CD/1000lm