



belux koi-s combines form and function in an astounding manner, because Naoto Fukasawa's credo "super normal design" reflects the design in a matter-of-fact way. The consistently slim-line construction makes v koi-s appear still more delicate and elegant. The luminaire family is thus particularly suitable for offices in which a cosier atmosphere is to be generated or for the home office. Despite its smaller size, belux koi-s provides an impressive 9000 lumens of non-directional LED light. For extra comfort, the direct and indirect light can be dimmed independently of each other. With a UGR of

Belux AG

www.belux.com
belux@belux.com

Type	KOIS10B-17-8030-MS
Order No	KOIS10B-17-8030-MS
Lamp type/assembly	Standing light
Colour	Chrome
Light source	LED
Colour temperature	3000 K
Colour rendering index	>80
Operating mode	Multisens
Operation	Self-adjusting
Ballast (number)	LED converter, integrated in luminaire head
Lamp head	PC, aluminium metallised
Diffuser	PC, prismaticised
Base	Die cast zinc, painted, black
Power cable	Black, 3x0.75mm ² , L 3000 mm
Mains plug	BS 1363 (type G)
Light distribution	Direct (33%) / indirect (67%)
UGR	<= 13
Total luminous flux of luminaire	8900 lm @ 4000 K
Power consumption	78W
Luminaire efficacy	114 lm/W
LED service life	55 000 h (L85/B30)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5 W
Safety class	I
Protection type	IP 20
Packaging units	3
Weight	9.9 kg
Guarantee	36 months

