
belux hello

Stephan Hürlemann




Type	Hello Flood
Order No	HEL14-12-8030
Lamp type/assembly	Cable system
Colour	White
Light source	LED
Colour temperature	3000 K
Colour rendering index	CRI > 90
Ballast (number)	External, 48 V DC
Lamp housing	Aluminium
Light distribution	Dicrect
Beam angle	Very wide flood
Total luminous flux of luminaire	1120 lm @ 3000 K
Power consumption	14 W
Luminaire efficacy	80 lm/W
LED service life	55 000 h (L85)
Tooltip Description	Tension wire system belux hello: supplied universal dowels and screws are suitable for fixation in solid brick or concrete walls (ceiling). For drywalls, plasterboard, suspended ceilings, cavity bricks, wooden cladding or similar, measures for reinforcement must be taken prior to installation. It is the responsibility of the installer/user to choose suitable fixation technology! When planning numerous light sources (spots, floods) the additional weight might force the tension wire to sag. belux therefore always recommends an intermediate suspension BL540 144 000 007 when planning system lengths >/= 5000mm.









Belux AG
Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com