belux u-turn

Michel Charlot






Type	UTN12-14-TD-8027
Order No	UTN12-14-TD-8027
Lamp type/assembly	Standing luminaire
Size	H 1335 mm
Light source	LED, 2x 900 lm
Colour temperature	2700 K
Colour rendering index	CRI > 80
Operating mode	Dimmable
Operation	On tube
Ballast (number)	Integrated in cable (1)
Lamp head	Die cast aluminum, wet painted, graphite black
Diffuser	PMMA, frosted on one side
Tube	Extruded aluminum profile, wet painted, graphite black
Base	Zinc die-cast, wet painted, graphite black
Finish	Black
Power cable	Black, L 2000 mm
Mains plug	Schuko plug type E+F
Light distribution	Direct
Beam angle	Adjustable 40° / 80°
Total luminous flux of luminaire	2x900 lm
Power consumption	2x 13W
Mains voltage	220-240V / 50Hz
Stand-by consumption	< 0,5 W
Safety class	I
Protection type	IP 20
Packaging units	1 (1600 x 300 x 300 mm)
Weight	10.5 kg
Guarantee	36 months


design preis schweiz


Swiss Federal Design Award

design arena preis 2013 gewinner

Leuchte des Jahres 2014







Belux AG
Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

?=97% cd/1000 lm