



| Type/Order No | CLD72-11-8030-DD |
|--|--|
| Lamp type/assembly | Pendant light |
| Light source | LED |
| Colour temperature | 3000 K |
| Colour rendering index | CRI > 80 |
| Chromaticity tolerance (initial MacAdam) | 3 SDCM initial |
| Operating mode | Dimmable DALI |
| Operation | On site |
| Ballast (number) | LED converter (2), built-in |
| Lamp shade | Polyester fleece |
| Length | 3 m |
| Suspension (number of suspension points) | max. 10000 mm (3) |
| Ceiling rose | White, Ø 108 mm |
| Power cable | Transparent, 5 x 1.5mm ² , L 10000 mm |
| Light distribution | Diffuse |
| Total luminous flux of luminaire | 18228 lm |
| Power consumption | 158 W |
| Luminaire efficacy | 116 lm/W |
| LED service life | 50 000 h (L80/F10) |
| Mains voltage | 220-240V / 50Hz |
| Stand-by consumption | < 0.5 W |
| Safety class | I |
| Protection type | IP 20 |
| Packaging units | 2 |
| Weight | 20.0 kg |
| Guarantee | 36 months |

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

