



Type	CLDXL-12-8040-DD
Order No	CLDXL-12-8040-DD
Lamp type/assembly	Pendant luminaire
Size	L 1500-1600 mm
Light source	LED
Colour temperature	4000 K
Colour rendering index	CRI > 80
Chromaticity tolerance (initial MacAdam)	3 SDCM
Operating mode	Dimmable DALI/Touchdim/On-Off
Operation	On site
Ballast (number)	DALI converter (1), integrated in luminaire
Lamp shade	Polyester fleece
Suspension (number of suspension points)	2
Ceiling rose	White, Ø 123 mm
Power cable	Transparent, 5 x 0.75mm ² , L 6000 mm
Light distribution	Diffuse
Total luminous flux of luminaire	8100 lm
Power consumption	70 W
Luminaire efficacy	115 lm/W
LED service life	50000 h (L80/F10)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5W
Safety class	I
Protection type	IP 20
Packaging units	1 (1550 x 650 x 320 mm)
Weight	10.0 kg
Tooltip Description	The fairweather cloud made from stable and mouldable material.
Guarantee	36 months

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

