
belux cloud

Frank Gehry, 2005







Type	CLD36-12-8027-DD
Order No	CLD36-12-8027-DD
Lamp type/assembly	Pendant luminaire
Size	Ø ~650 mm
Light source	LED
Colour temperature	2700 K
Colour rendering index	CRI > 80
Chromaticity tolerance (initial MacAdam)	3 SDCM
Operating mode	Dimmable DALI/Touchdim/On-Off
Operation	On site
Ballast (number)	DALI converter (1), integrated in luminaire
Lamp shade	Polyester fleece
Suspension (number of suspension points)	1
Ceiling rose	White, Ø 123 mm
Power cable	Transparent, 5 x 0.75mm^2 , L 5500 mm
Light distribution	Diffuse
Total luminous flux of luminaire	2900 lm @ 3000 K
Power consumption	37 W
Luminaire efficacy	78 lm/W @ 3000 K
LED service life	50 000 h (L80/F10)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5W
Safety class	I
Protection type	IP 20
Packaging units	1 (470 x 420 x 400 mm)
Weight	2.3 kg
Guarantee	5 years

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

