



| | |
|--|--|
| Type | CLD36-12-8040-DD |
| Order No | CLD36-12-8040-DD |
| Lamp type/assembly | Pendant luminaire |
| Size | Ø ~650 mm |
| Light source | LED |
| Colour temperature | 4000 K |
| Colour rendering index | CRI > 80 |
| Chromaticity tolerance (initial MacAdam) | 3 SDCM |
| Operating mode | Dimmable DALI/Touchdim/On-Off |
| Operation | On site |
| Ballast (number) | DALI converter (1), integrated in luminaire |
| Lamp shade | Polyester fleece |
| Suspension (number of suspension points) | 1 |
| Ceiling rose | White, Ø 123 mm |
| Power cable | Transparent, 5 x 0.75mm ² , L 5500 mm |
| Light distribution | Diffuse |
| Total luminous flux of luminaire | 2900 lm @ 3000 K |
| Power consumption | 37 W |
| Luminaire efficacy | 78 lm/W @ 3000 K |
| LED service life | 50 000 h (L80/F10) |
| Mains voltage | 220-240V, 50Hz |
| Stand-by consumption | < 0.5W |
| Safety class | I |
| Protection type | IP 20 |
| Packaging units | 1 (470 x 420 x 400 mm) |
| Weight | 2.3 kg |
| Guarantee | 36 months |

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

