




Type	CLD10-11-8030-TD
Order No	CLD10-11-8030-TD
Lamp type/assembly	Standing luminaire
Size	H 1700 mm
Light source	LED
Colour temperature	3000 K
Colour rendering index	CRI > 80
Chromaticity tolerance (initial MacAdam)	3 SDCM
Operating mode	Dimmable
Operation	At the base
Ballast (number)	DALI converter (1), integrated in luminaire
Lamp shade	Polyester fleece
Tube	Stainless steel, fine-grain polished
Base	White alu, matt, wet-painted
Power cable	Transparent, 2 x 0.75mm ² , L 2500 mm
Mains plug	Euro-plug Typ C
Light distribution	Diffuse
Total luminous flux of luminaire	2867 lm @ 3000 K
Power consumption	37 W
Luminaire efficacy	77 lm/W @ 3000 K
LED service life	50 000 h (L80/F10)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5W
Safety class	II
Protection type	IP 20
Packaging units	1 (1450 x 490 x 320 mm)
Weight	9.3 kg
Guarantee	36 months

Belux AG
Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

