



<b>Type</b>	<b>OBO30-11-8040-TD</b>
Order No	OBO30-11-8040-TD
Lamp type/assembly	Pendant luminaire
Size	L 1290 mm
Light source	LED
Colour temperature	4000 K
Colour rendering index	CRI > 80
Chromaticity tolerance (initial MacAdam)	3 SDCM
Operating mode	Dimmable
Operation	On lamp
Ballast (number)	DALI converter (1), integrated in luminaire
Lamp shade	Polyester fleece
Suspension (number of suspension points)	max. 2000 mm (2)
Ceiling rose	White, Ø 108 mm
Power cable	Transparent, 3 x 0.75mm <sup>2</sup> , L 2500 mm
Light distribution	Diffuse
Total luminous flux	7800 lm @ 4000 K
Power consumption	60 W
Luminaire efficacy	130 lm/W
LED service life	50 000 h (L80/F10)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5W
Safety class	I
Protection type	IP 20
Packaging units	1 (1720 x 160 x 160 mm)
Weight	3.5 kg
Tooltip Description	High-quality materials, an energy-saving lamp and a unique interplay of light and shadow
Guarantee	36 months

**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com



reddot



≈81% CD/1000lm