



|  |  |
|--|--|
| <b>Type</b>                              | <b>OBO30-11-8027-DD</b>  |
| Order No                                 | OBO30-11-8027-DD   |
| Lamp type/assembly                       | Pendant luminaire  |
| Size                                     | L 1290 mm  |
| Light source                             | LED  |
| Colour temperature                       | 2700K  |
| Colour rendering index                   | CRI > 80   |
| Chromaticity tolerance (initial MacAdam) | 3 SDCM   |
| Operating mode                           | Dimmable DALI  |
| Operation                                | On remote  |
| Ballast (number)                         | DALI converter (1), integrated in luminaire  |
| Lamp shade                               | Polyester fleece   |
| Suspension (number of suspension points) | max. 2000 mm (2)   |
| Ceiling rose                             | White, Ø 108 mm  |
| Power cable                              | Transparent, 5 x 0.75mm <sup>2</sup> , L 2500 mm   |
| Light distribution                       | Diffuse  |
| Total luminous flux                      | 4900 lm @ 3000K  |
| Power consumption                        | 60 W   |
| Luminaire efficacy                       | 82 lm/W  |
| LED service life                         | 50 000 h (L80/F10)   |
| Mains voltage                            | 220-240V, 50Hz   |
| Stand-by consumption                     | < 0.5W   |
| Safety class                             | I  |
| Protection type                          | IP 20  |
| Packaging units                          | 1 (1720 x 160 x 160 mm)  |
| Weight                                   | 3.5 kg   |
| Tooltip Description                      | High-quality materials, an energy-saving lamp and a unique interplay of light and shadow |
| Guarantee                                | 36 months  |

**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com



reddot



≈81% CD/1000lm