



Type	OBO32-11-8030-DD
Order No	OBO32-11-8030-DD
Lamp type/assembly	Pendant luminaire
Size	L 1590 mm
Light source	LED
Colour temperature	3000K
Colour rendering index	CRI > 80
Chromaticity tolerance (initial MacAdam)	3 SDCM
Operating mode	Dimmable DALI
Operation	On remote
Ballast (number)	DALI converter (1), integrated in luminaire
Lamp shade	Polyester fleece
Suspension (number of suspension points)	max. 2000 mm (2)
Ceiling rose	White, Ø 108 mm
Power cable	Transparent, 5 x 0.75mm ² , L 2500 mm
Light distribution	Diffuse
Total luminous flux	6000 lm @ 3000K
Power consumption	75 W
Luminaire efficacy	80 lm/W
LED service life	50 000 h (L80/F10)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5W
Safety class	I
Protection type	IP 20
Packaging units	1 (1720 x 160 x 160 mm)
Weight	4.34 kg
Tooltip Description	High-quality materials, an energy-saving lamp and a unique interplay of light and shadow
Guarantee	36 months

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com



red dot



≈81% CD/1000lm