



Type	OBO01-11-8027-TD
Order No	OBO01-11-8027-TD
Lamp type/assembly	Standing luminaire
Size	H 1500 mm
Light source	LED
Colour temperature	2700K
Colour rendering index	CRI > 80
Chromaticity tolerance (initial MacAdam)	3 SDCM
Operating mode	Dimmable
Operation	On lamp
Ballast (number)	DALI converter (1), integrated in luminaire
Lamp shade	Polyester fleece
Base	Steel, white-aluminium, powder-coated
Power cable	Black, 3 x 0.75mm ² , L 3000 mm
Mains plug	Swiss plug type J
Light distribution	Diffuse
Total luminous flux	2550 lm @ 3000K
Power consumption	64 W
Luminaire efficacy	37 lm/W
LED service life	50 000 h (L80/F10)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5W
Safety class	I
Protection type	IP 20
Packaging units	1 (1550 x 410 x 360 mm)
Weight	15.0 kg
Tooltip Description	High-quality materials, an energy-saving lamp and a unique interplay of light and shadow
Guarantee	36 months
Belux Express	Small quantities normally available from stock

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com



≈39.79% CD/1000lm