



| | |
|--|--|
| Type | DIO10-12-8027-TD |
| Order No | DIO10-12-8027-TD |
| Lamp type/assembly | Standing luminaire |
| Colour | Bronze |
| Light source | LED |
| Colour temperature | 2700 K |
| Colour rendering index | CRI > 90 |
| Chromaticity tolerance (initial MacAdam) | 3 SDCM |
| Operating mode | Dimmable |
| Operation | On stand |
| Ballast (number) | Integrated in luminaire |
| Lamp head | Aluminium extruded |
| Tube | Aluminium extruded |
| Base | Aluminium |
| Finish | Wet-painted |
| Power cable | Black, L 3000 mm |
| Mains plug | Schuko plug type E+F |
| Light distribution | Direct / indirect |
| Total luminous flux | 630 + 4625 lm |
| Power consumption | 50 W |
| LED service life | 50 000 h (L80/F10) |
| Mains voltage | 220-240V, 50Hz |
| Stand-by consumption | < 0.5 W |
| Safety class | I |
| Protection type | IP 20 |
| Packaging units | 1 (1880 x 400 x 360 mm) |
| Weight | 14,5 kg |
| Tooltip Description | The indirect lamp with adjustable reading light. |
| Guarantee | 36 months |

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

