






Type	KOI30-14-8030-TD
Order No	KOI30-14-8030-TD
Lamp type/assembly	Pendant light
Colour	White
Colour temperature	3000 K
Colour rendering index	> 85
Operating mode	Dimmable TD
Operation	On site
Ballast (number)	LED Converter (2), integrated in luminaire head
Lamp head	PC, painted, white
Diffuser	PC, prismaticed, dyed white
Suspension (number of suspension points)	500 mm (1)
Suspension tube	Steel, powder-coated, white
Ceiling rose	PA, painted, white, Ø 109 mm
Power cable	Black, 5x0.75mm <sup>2</sup> , L ~300 mm
Light distribution	Direct (27%) / indirect (73%)
UGR	< 19
Total luminous flux of luminaire	10688 lm @ 4000 K
Power consumption	83 W
Luminaire efficacy	128 lm/W @ 4000 K
LED service life	55 000 h (L85)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5 W
Safety class	I
Protection type	IP 20
Packaging units	2 (ca. 600 x 600 x 230 + 780/1280 x 200 x 50 mm)
Weight	8.4 kg
Guarantee	36 months

KOI30-14-8030-TD

MINERGIE®



**Belux AG**

Neufeldweg 6, CH-5103 Möriken  
 Tel. +41 61 316 74 01  
 Fax +41 61 316 75 99  
 www.belux.com  
 belux@belux.com