



<b>Type</b>	<b>DIO10-11-8027-TD</b>
Order No	DIO10-11-8027-TD
Lamp type/assembly	Standing luminaire
Colour	Bronze
Light source	LED
Colour temperature	2700 K
Colour rendering index	CRI > 80
Chromaticity tolerance (initial MacAdam)	3 SDCM
Operating mode	Dimmable
Operation	On stand
Ballast (number)	Integrated in luminaire
Lamp head	Aluminium extruded
Tube	Aluminium extruded
Base	Aluminium
Finish	Wet-painted
Power cable	Black, L 3000 mm
Mains plug	Swiss plug type J
Light distribution	Direct / indirect
Total luminous flux	630 + 4625 lm
Power consumption	50 W
LED service life	50 000 h (L80/F10)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5 W
Safety class	I
Protection type	IP 20
Packaging units	1 (1880 x 400 x 360 mm)
Weight	14,5 kg
Tooltip Description	The indirect lamp with adjustable reading light.
Guarantee	36 months

**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com

