



belux disk




Type/Order No	DIS30-15-TD
Lamp type/assembly	Pendant light
Colour	White
Light source	1x T5 FC (FC) 55W; 2Gx13 + 1x T5 FC (FC) 60W; 2Gx13
Operating mode	Dimmable
Operation	On site
Ballast (number)	Electronic ballast dimmable (2)
Lamp head	Aluminium die-cast
Diffuser	PMMA lens
Suspension (number of suspension points)	max. 2000 / 5000 mm (3)
Ceiling rose	White, Ø 108 mm
Power cable	White, 5x0.75mm ² , L 2400 / 5400 mm
Light distribution	Direct (26.8%) / indirect (73.2%)
Power consumption	115 W
Luminaire efficacy	80.06%
Mains voltage	220-240V, 50/60Hz
Stand-by consumption	< 0.5W
Safety class	I
Protection type	IP 20
Packaging units	1 (480 x 480 x 140 mm)
Weight	4.0 kg
Guarantee	36 months

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

MINERGIE®

light of
the future



η=80.06% CD/1000lm

www.belux.com/disk