



# belux disk




Type/Order No	DIS10-18-MS
Lamp type/assembly	Standing light
Colour	Chrome
Light source	1x T5 FC (FC) 55W; 2Gx13 + 1x T5 FC (FC) 60W; 2Gx13
Operating mode	Multisens
Operation	Self-adjusting
Ballast (number)	Electronic ballast dimmable (2)
Lamp head	Aluminium die-cast
Diffuser	PMMA lens
Tube	Steel, chrome-plated
Base	Round base, steel, black, powder-coated
Power cable	Transparent, 3x0.75mm <sup>2</sup> , L 3000 mm
Mains plug	UK plug type G
Light distribution	Direct (26.8%) / indirect (73.2%)
Power consumption	115 W
Luminaire efficacy	80.06%
Mains voltage	220-240V, 50/60Hz
Stand-by consumption	< 0.5W
Safety class	I
Protection type	IP 20
Packaging units	2 (480 x 480 x 140 mm + 1920 x 100 x 100 mm)
Weight	12.7 kg
Guarantee	36 months

## Belux AG

Neufeldweg 6, CH-5103  
Mörlikon  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com

**MINERGIE®**

light of  
the future



η=80.06% CD/1000lm

[www.belux.com/disk](http://www.belux.com/disk)