



<b>Type/Order No</b>	<b>FLA12-12-TD</b>
Lamp type/assembly	Standing light
Version	With arm (asymmetrical); head 350° pivotal
Light source	4x TC-L (FSDH) 55W; 2G11
Operating mode	Dimmable
Operation	On lamp head
Ballast (number)	Electronic ballast dimmable (2)
Lamp head	Aluminium die-cast, alu-coloured, wet painted
Diffuser	PMMA, prismatic, metallised
Tube	Steel, alu-coloured, wet painted
Base	Steel, black, powder-coated
Power cable	Black, 3x0.75mm <sup>2</sup> , L 5000 mm
Mains plug	Schuko plug type E+F
Light distribution	Direct (31.5%) / indirect (68.5%)
Power consumption	220 W
Luminaire efficacy	81.5%
Mains voltage	230V/50Hz
Stand-by consumption	< 0.5W
Safety class	I
Protection type	IP 20
Packaging units	3 (1950 x 150 x 150 + 800 x 400 x 250 + 420 x 330 x 150 mm)
Weight	20.5 kg
Guarantee	36 months

**Belux AG**  
 Neufeldweg 6, CH-5103  
 Möriken  
 Tel. +41 61 316 74 01  
 Fax +41 61 316 75 99  
 www.belux.com  
 belux@belux.com



MINERGIE®

red dot



η=81.5% CD/1000lm