



Type	KOIS10B-11-8030-MS
Order No	KOIS10B-11-8030-MS
Lamp type/assembly	Standing luminaire
Colour	Chrome
Light source	LED
Colour temperature	3000 K
Colour rendering index	>80
Operating mode	Multisens
Operation	Self-adjusting
Ballast (number)	LED converter, integrated in luminaire head
Lamp head	PC, aluminium metallised
Diffuser	PC, prismaticised
Base	X-shaped base, steel, powder-coated, black
Power cable	Black, 3x0.75mm <sup>2</sup> , L 3000 mm
Mains plug	Swiss T12 (type J)
Light distribution	Direct (33%) / indirect (67%)
UGR	<= 13
Total luminous flux of luminaire	8900 lm @ 4000 K
Power consumption	78W
Luminaire efficacy	114 lm/W
LED service life	55 000 h (L85/B30)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5 W
Safety class	I
Protection type	IP 20
Packaging units	3
Weight	9.9 kg
Tooltip Description	The smart light point
Guarantee	36 months

**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com

