



Type	KOIS10-14-8040-MS
Order No	KOIS10-14-8040-MS
Lamp type/assembly	Standing light
Colour	Chrome
Light source	LED
Colour temperature	4000 K
Colour rendering index	>80
Operating mode	Multisens
Operation	Self-adjusting
Ballast (number)	Converter, integrated in luminaire base
Lamp head	PC, aluminium metallised
Diffuser	PC, prismaticed
Base	Die cast zinc, painted, black
Power cable	Black, 3x0.75mm ² , L 3000 mm
Mains plug	CEE 7/7 AC plug (type E+F)
Light distribution	Direct (31%) / indirect (69%)
UGR	<16 (4H/8H)
Total luminous flux of luminaire	7062 lm @ 4000 K
Power consumption	77 W
Luminaire efficacy	92 lm/W
LED service life	55 000 h (L85/B30)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5 W
Safety class	I
Protection type	IP 20
Packaging units	1
Guarantee	36 months

KOIS10-14-8040-MS



Belux AG
 Neufeldweg 6, CH-5103 Möriken
 Tel. +41 61 316 74 01
 Fax +41 61 316 75 99
www.belux.com
belux@belux.com