



| Type/Order No | KOIS30-13-8040-DD |
|----------------------------------|---------------------------------------|
| Lamp type/assembly | Pendant light |
| Colour | Chrome |
| Light source | LED |
| Colour temperature | 4000 K |
| Colour rendering index | >80 |
| Operating mode | Dimmable DALI |
| Operation | On site |
| Ballast (number) | Converter, integrated in ceiling rose |
| Lamp head | PC, aluminium metallised |
| Diffuser | PC, prismaticised |
| Tube | Steel, chrome-plated |
| Suspension tube | Steel, chrome-plated |
| Ceiling rose | PA, black or white, Ø 170 mm |
| Light distribution | Direct (31%) / indirect (69%) |
| UGR | <16 (4H/8H) |
| Total luminous flux of luminaire | 7062 lm @ 4000 K |
| Power consumption | 77 W |
| Luminaire efficacy | 92 lm/W |
| LED service life | 55 000 h (L85/B30) |
| Mains voltage | 220-240V, 50Hz |
| Stand-by consumption | < 0.5 W |
| Safety class | I |
| Protection type | IP 20 |
| Packaging units | 2 |
| Weight | 5.1 kg |
| Guarantee | 36 months |

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

