





Type	KOIS30-19-8040-DD
Order No	KOIS30-19-8040-DD
Lamp type/assembly	Pendant light
Colour	White
Light source	LED
Colour temperature	4000 K
Colour rendering index	>80
Operating mode	Dimmable DALI
Operation	On site
Ballast (number)	Converter, integrated in ceiling rose
Lamp head	PC, painted, white
Diffuser	PC, prismatic
Suspension tube	Steel, powder-coated, white
Ceiling rose	PA, white, Ø 170 mm
Light distribution	Direct (31%) / indirect (69%)
UGR	<16 (4H/8H)
Total luminous flux of luminaire	7062 lm @ 4000 K
Power consumption	77 W
Luminaire efficacy	92 lm/W
LED service life	55 000 h (L85/B30)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5 W
Safety class	I
Protection type	IP 20
Packaging units	2
Guarantee	36 months

**KOIS30-19-8040-DD**



**Belux AG**  
 Neufeldweg 6, CH-5103 Möriken  
 Tel. +41 61 316 74 01  
 Fax +41 61 316 75 99  
[www.belux.com](http://www.belux.com)  
[belux@belux.com](mailto:belux@belux.com)