



| Type/Order No                    | KOIS43-15-8030-MS                        |
|----------------------------------|--|
| Lamp type/assembly               | Desk-mounted luminaire                   |
| Version                          | USM Haller                               |
| Adaptation point                 | At the table leg                         |
| Cable exit                       | Lateral                                  |
| Colour                           | Chrome                                   |
| Light source                     | LED                                      |
| Colour temperature               | 3000 K                                   |
| Colour rendering index           | >80                                      |
| Operating mode                   | Multisens                                |
| Operation                        | Self-adjusting                           |
| Ballast (number)                 | Converter, cable integrated              |
| Lamp head                        | PC, aluminium metallised                 |
| Diffuser                         | PC, prismaticised                        |
| Tube                             | Steel, chrome-plated                     |
| Power cable                      | Black, 3x0.75mm <sup>2</sup> , L 3000 mm |
| Mains plug                       | BS 1363 (type G)                         |
| Light distribution               | Direct (31%) / indirect (69%)            |
| UGR                              | <16 (4H/8H)                              |
| Total luminous flux of luminaire | 7062 lm @ 4000 K                         |
| Power consumption                | 77 W                                     |
| Luminaire efficacy               | 92 lm/W                                  |
| LED service life                 | 55 000 h (L85/B30)                       |
| Mains voltage                    | 220-240V, 50Hz                           |
| Stand-by consumption             | < 0.5 W                                  |
| Safety class                     | I  |
| Protection type                  | IP 20                                    |
| Packaging units                  | 1  |
| Guarantee                        | 36 months                                |

**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com

