



<b>Type</b>	<b>KOIS46B-18-8030-MS</b>
Order No	KOIS46B-18-8030-MS
Lamp type/assembly	Desk-mounted luminaire
Version	Universal-D
Adaptation point	For permanent fastening to any tabletop
Cable exit	Underneath the tabletop
Colour	Black
Light source	LED
Colour temperature	3000 K
Colour rendering index	>80
Operating mode	Multisens
Operation	Self-adjusting
Ballast (number)	LED converter, cable integrated
Lamp head	PC, painted
Diffuser	PC, prismatic
Tube	Steel, black, powder-coated
Power cable	Black, 3x0.75mm <sup>2</sup> , L 3000 mm
Mains plug	UK plug type G
UGR	</= 13
Total luminous flux of luminaire	8900 lm @ 4000 K
Power consumption	78W
Luminaire efficacy	114 lm/W
LED service life	55 000 h (L85/B30)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5 W
Safety class	I
Protection type	IP 20
Packaging units	1
Weight	8.2 kg
Guarantee	36 months

**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com

