



| Type | KOIS46B-19-8030-TD |
|----------------------------------|--|
| Order No | KOIS46B-19-8030-TD |
| Lamp type/assembly | Desk-mounted luminaire |
| Version | Universal-D |
| Adaptation point | For permanent fastening to any tabletop |
| Cable exit | Underneath the tabletop |
| Colour | White |
| Light source | LED |
| Colour temperature | 3000 K |
| Colour rendering index | >80 |
| Operating mode | Dimmable |
| Operation | On tube |
| Ballast (number) | LED converter, cable integrated |
| Lamp head | PC, painted |
| Diffuser | PC, prismatic |
| Tube | Steel, white, powder-coated |
| Power cable | Black, 3x0.75mm ² , L 3000 mm |
| Mains plug | BS 1363 (type G) |
| UGR | </= 13 |
| Total luminous flux of luminaire | 8900 lm @ 4000 K |
| Power consumption | 78W |
| Luminaire efficacy | 114 lm/W |
| LED service life | 55 000 h (L85/B30) |
| Mains voltage | 220-240V, 50Hz |
| Stand-by consumption | < 0.5 W |
| Safety class | I |
| Protection type | IP 20 |
| Packaging units | 1 |
| Weight | 8.2 kg |
| Tooltip Description | The smart light point |
| Guarantee | 36 months |

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

