



| Type                             | Hello Spot (40°)   |
|----------------------------------|--|
| Order No                         | HEL06-13-8030  |
| Lamp type/assembly               | Cable system   |
| Colour                           | Black  |
| Light source                     | LED  |
| Colour temperature               | 3000 K   |
| Colour rendering index           | CRI > 90   |
| Ballast (number)                 | External, 48 V DC  |
| Lamp housing                     | Aluminium  |
| Light distribution               | Direct   |
| Beam angle                       | 40°  |
| Total luminous flux of luminaire | 490 lm @ 3000 K  |
| Power consumption                | 6 W  |
| Luminaire efficacy               | 82 lm/W  |
| LED service life                 | 55 000 h (L85)   |
| Tooltip Description              | <p>Tension wire system <span class="wordmark-r">belux</span></p> <p>hello: supplied universal dowels and screws are suitable for fixation in solid brick or concrete walls (ceiling). For drywalls, plasterboard, suspended ceilings, cavity bricks, wooden cladding or similar, measures for reinforcement must be taken prior to installation. It is the responsibility of the installer/user to choose suitable fixation technology!</p> <p>When planning numerous light sources (spots, floods) the additional weight might force the tension wire to sag.</p> <p><span class="wordmark-r">belux</span> therefore always recommends an intermediate suspension BL540 144 000 007 when planning system lengths <math>\geq 5000\text{mm}</math>.</p> |

**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com

