



Type	Hello Spot (40°)
Order No	HEL06-14-8027
Lamp type/assembly	Cable system
Colour	White
Light source	LED
Colour temperature	2700 K
Colour rendering index	CRI > 90
Ballast (number)	External, 48 V DC
Lamp housing	Aluminium
Light distribution	Direct
Beam angle	40°
Total luminous flux of luminaire	490 lm @ 3000 K
Power consumption	6 W
Luminaire efficacy	82 lm/W
LED service life	55 000 h (L85)
Tooltip Description	<p>Tension wire system belux</p> <p>hello: supplied universal dowels and screws are suitable for fixation in solid brick or concrete walls (ceiling). For drywalls, plasterboard, suspended ceilings, cavity bricks, wooden cladding or similar, measures for reinforcement must be taken prior to installation. It is the responsibility of the installer/user to choose suitable fixation technology!</p> <p>When planning numerous light sources (spots, floods) the additional weight might force the tension wire to sag.</p> <p>belux therefore always recommends an intermediate suspension BL540 144 000 007 when planning system lengths $\geq 5000\text{mm}$.</p>

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

