



| | |
|----------------------------------|--|
| Type | KOI43-12-8040-MS |
| Order No | KOI43-12-8040-MS |
| Lamp type/assembly | Table light |
| Version | for "USM Haller" |
| Adaptation point | At the table leg |
| Cable exit | Lateral |
| Colour | Chrome |
| Colour temperature | 4000 K |
| Colour rendering index | > 85 |
| Operating mode | Multisens |
| Operation | Self-adjusting |
| Ballast (number) | LED Converter (2), integrated in luminaire head |
| Lamp head | PC, aluminium metallised |
| Diffuser | PC, prismaticed, dyed white |
| Tube | Steel, chrome-plated |
| Power cable | Black, 3x0.75mm ² , L 5000 mm (1000 mm with Wieland GST18 connector + 4000 mm with Wieland GST18 socket and plug) |
| Mains plug | CEE 7/7 (type E+F) |
| Light distribution | Direct (27%) / indirect (73%) |
| UGR | < 19 |
| Total luminous flux of luminaire | 10688 lm @ 4000 K |
| Power consumption | 83 W |
| Luminaire efficacy | 128 lm/W @ 4000 K |
| LED service life | 55 000 h (L85) |
| Mains voltage | 220-240V, 50Hz |
| Stand-by consumption | < 0.5 W |
| Safety class | I |
| Protection type | IP 20 |
| Packaging units | 2 (ca. 600 x 600 x 230 + 1550 x 200 x 50 mm) |
| Weight | 10.3 kg |
| Remark | Not con tables, height-ac |
| Guarantee | 36 months |

KOI43-12-8040-MS

MINERGIE®



Belux AG
 Neufeldweg 6, CH-5103 Möriken
 Tel. +41 61 316 74 01
 Fax +41 61 316 75 99
 www.belux.com
 belux@belux.com