



| | |
|----------------------------------|---|
| Type | KOIQ10B-12-8040-MS |
| Order No | KOIQ10B-12-8040-MS |
| Lamp type/assembly | Standing luminaire |
| Colour | Black |
| Light source | LED |
| Colour temperature | 4000 K |
| Colour rendering index | >80 |
| Operating mode | Multisens |
| Operation | Self-adjusting |
| Ballast (number) | LED converter, integrated in luminaire head |
| Lamp head | PC, painted |
| Diffuser | PC, prismatic |
| Base | Die cast zinc, painted |
| Power cable | Black, 3x0.75mm ² , L 3000 mm |
| Mains plug | Swiss T12 (type J) |
| Light distribution | Direct (33%) / indirect (67%) |
| UGR | <= 13 |
| Total luminous flux of luminaire | 8900 lm @ 4000 K |
| Power consumption | 78W |
| Luminaire efficacy | 114 lm/W |
| LED service life | 55 000 h (L85/B30) |
| Mains voltage | 220-240V, 50Hz |
| Stand-by consumption | < 0.5 W |
| Safety class | I |
| Protection type | IP 20 |
| Packaging units | 3 |
| Weight | 9.9 kg |
| Tooltip Description | The smart light square |
| Guarantee | 36 months |

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

