



| Type | KOIQ30B-16-8030-MS |
|----------------------------------|---------------------------------------|
| Order No | KOIQ30B-16-8030-MS |
| Lamp type/assembly | Pendant luminaire |
| Colour | Black |
| Light source | LED |
| Colour temperature | 3000 K |
| Colour rendering index | >80 |
| Operating mode | Multisens |
| Operation | Self-adjusting |
| Ballast (number) | Converter, integrated in ceiling rose |
| Lamp head | PC, painted |
| Diffuser | PC, prismatic |
| Suspension tube | Steel, powder-coated, black |
| Ceiling rose | PA, black, Ø 170 mm |
| UGR | </= 13 |
| Total luminous flux of luminaire | 5970 lm @ 4000 K |
| Power consumption | 78W |
| Luminaire efficacy | 114 lm/W |
| LED service life | 55 000 h (L85/B30) |
| Mains voltage | 220-240V, 50Hz |
| Stand-by consumption | < 0.5 W |
| Safety class | I |
| Protection type | IP 20 |
| Packaging units | 2 |
| Weight | 5.1 kg |
| Guarantee | 36 months |

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

