



<b>Type</b>	<b>UTN12-12-TD-8027</b>
Order No	UTN12-12-TD-8027
Lamp type/assembly	Standing luminaire
Size	H 1335 mm
Light source	LED, 2x 900 lm
Colour temperature	2700 K
Colour rendering index	CRI > 80
Operating mode	Dimmable
Operation	On tube
Ballast (number)	Integrated in cable (1)
Lamp head	Die cast aluminum, wet painted, graphite black
Diffuser	PMMA, frosted on one side
Tube	Extruded aluminum profile, wet painted, graphite black
Base	Zinc die-cast, wet painted, graphite black
Finish	Black
Power cable	Black, L 2000 mm
Mains plug	Swiss plug type J
Light distribution	Direct
Beam angle	Adjustable 40° / 80°
Total luminous flux of luminaire	2x900 lm
Power consumption	2x 13W
Mains voltage	220-240V / 50Hz
Stand-by consumption	< 0,5 W
Safety class	I
Protection type	IP 20
Packaging units	1 (1600 x 300 x 300 mm)
Weight	10,5 kg
Guarantee	36 months

**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com

design  
preis  
SCHWEIZ

