



Type/Order No	UTN10-13-TD-8027
Lamp type/assembly	Standing light
Size	H 1150 mm
Energy efficiency class	A
Light source	LED, 1x 900 lm
Colour temperature	2700 K
Colour rendering index	CRI > 80
Operating mode	Dimmable
Operation	On tube
Ballast (number)	Driver (1), cable integrated
Lamp head	Die cast aluminum, wet painted, telegrey
Diffuser	PMMA, frosted on one side
Tube	Extruded aluminum profile, wet painted, telegrey
Base	Zinc die-cast, wet painted, telegrey
Finish	Telegrey
Power cable	Black, L 2000 mm
Mains plug	Schuko plug type E+F
Light distribution	Direct
Beam angle	Adjustable 40° / 80°
Total luminous flux of luminaire	900 lm
Power consumption	13W
Mains voltage	220-240V / 50Hz
Stand-by consumption	< 0,5 W
Safety class	I
Protection type	IP 20
Packaging units	1 (1220 x 270 x 270 mm)
Weight	8.4 kg
Guarantee	36 months

Belux AG
 Neufeldweg 6, CH-5103
 Möriken
 Tel. +41 61 316 74 01
 Fax +41 61 316 75 99
 www.belux.com
 belux@belux.com

design
preis
schweiz

