



<b>Type</b>	<b>MBM-84-8040-DD</b>
Order No	MBM-84-8040-DD
Lamp type/assembly	System luminaire
Description	Light unit
Light source	LED
Colour temperature	4000 K
Colour rendering index	CRI > 80
Chromaticity tolerance (initial MacAdam)	3 SDCM initial
Operating mode	Dimmable DALI
Ballast (number)	LED converter (1), integrated in luminaire
Feed-through wiring	5 x 1.5 mm <sup>2</sup>
Length	853 mm
Lamp housing	Aluminium, anodised
Diffuser	PMMA
End cap	With built-in plug/socket for electrical through-connection
Total luminous flux of luminaire	1125 lm @ 3000 K
Power consumption	15 W
Luminaire efficacy	75 lm/W @ 3000 K
LED service life	60 000 h (L80/B50) @ 65° C
Mains voltage	220-240V / 50Hz
Stand-by consumption	< 0.5 W
Safety class	I
Protection type	IP 20
Packaging units	1
Tooltip Description	Light by the metre with limitless possibilities
Remark	Light unit designed for use in the meter by meter carrier profile
Guarantee	36 months
Included accessories	Fastening clips

**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com

