



| Type/Order No | MBM-140-8040-00 |
|--|---|
| Lamp type/assembly | System component |
| Description | Light unit |
| Light source | LED |
| Colour temperature | 4000 K |
| Colour rendering index | CRI > 80 |
| Chromaticity tolerance (initial MacAdam) | 3 SDCM initial |
| Operating mode | On/Off |
| Ballast (number) | LED converter (1), integrated in luminaire |
| Feed-through wiring | 3 x 1.5 mm ² |
| Length | 1413 mm |
| Lamp housing | Aluminium, anodised |
| Diffuser | PMMA |
| End cap | With built-in plug/socket for electrical through-connection |
| Total luminous flux of luminaire | 1875 lm @ 3000 K |
| Power consumption | 25 W |
| Luminaire efficacy | 75 lm/W @ 3000 K |
| LED service life | 60 000 h (L80/B50) @ 65° C |
| Mains voltage | 220-240V / 50Hz |
| Stand-by consumption | < 0.5 W |
| Safety class | I |
| Protection type | IP 20 |
| Packaging units | 1 |
| Remark | Light unit designed for use in the meter by meter carrier profile |
| Guarantee | 36 months |
| Included accessories | Fastening clips |

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com



red dot
best of the best