




Type	MBM-84-8027-1-10
Order No	MBM-84-8027-1-10
Lamp type/assembly	System luminaire
Description	Light unit
Light source	LED
Colour temperature	2700 K
Colour rendering index	CRI > 80
Chromaticity tolerance (initial MacAdam)	3 SDCM initial
Operating mode	Dimmable 1-10V
Ballast (number)	LED converter (1), integrated in luminaire
Feed-through wiring	5 x 1.5 mm ²
Length	853 mm
Lamp housing	Aluminium, anodised
Diffuser	PMMA
End cap	With built-in plug/socket for electrical through-connection
Total luminous flux of luminaire	1125 lm @ 3000 K
Power consumption	15 W
Luminaire efficacy	75 lm/W @ 3000 K
LED service life	60 000 h (L80/B50) @ 65° C
Mains voltage	220-240V / 50Hz
Stand-by consumption	< 0.5 W
Safety class	I
Protection type	IP 20
Packaging units	1
Tooltip Description	Light by the metre with limitless possibilities
Remark	Light unit designed for use in the meter by meter carrier profile
Guarantee	36 months
Included accessories	Fastening clips

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

