



Type/Order No	KOI10-18-8030-TD
Lamp type/assembly	Standing light
Colour	Black
Colour temperature	3000 K
Colour rendering index	>/= 80
Operating mode	Dimmable
Operation	2 circuit push-button, integrated in stand
Lamp head	PC, painted, black
Diffuser	PC, prismatic, dyed white
Tube	Steel, black, powder-coated
Base	X-shaped base; steel, powder-coated, black
Power cable	Black, 3x0.75mm <sup>2</sup> , L 5000 mm
Mains plug	CEE 7/7 (type E+F)
Light distribution	Direct (27%) / indirect (73%)
UGR	< 19
Total luminous flux of luminaire	11825 lm @ 4000 K
Power consumption	83 W
Luminaire efficacy	128 lm/W @ 4000 K
LED service life	55 000 h (L85)
Mains voltage	220-240V, 50Hz
Stand-by consumption	< 0.5 W
Safety class	I
Protection type	IP 20
Packaging units	3 (ca. 600 x 600 x 230 + 2250 x 230 x 50 + 750 x 650 x 50 mm)
Weight	20.7 kg
Guarantee	36 months

**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com

**MINERGIE®**

