




| | |
|------------------------------------------|--------------------------------------------------|
| Type | KOI30-19-8030-TD |
| Order No | KOI30-19-8030-TD |
| Lamp type/assembly | Pendant luminaire |
| Colour | Black |
| Colour temperature | 3000 K |
| Colour rendering index | >= 80 |
| Operating mode | Dimmable TD |
| Operation | On site |
| Ballast (number) | LED Converter (2), integrated in luminaire head |
| Lamp head | PC, black, painted |
| Diffuser | PC, prismatic, dyed white |
| Suspension (number of suspension points) | 2000 mm (1) |
| Suspension tube | Steel, black, powder-coated |
| Ceiling rose | PA, painted, black, Ø 109 mm |
| Power cable | Black, 5x0.75mm ² , L ~300 mm |
| Light distribution | Direct (27%) / indirect (73%) |
| UGR | < 19 |
| Total luminous flux of luminaire | 11825 lm @ 4000 K |
| Power consumption | 90 W |
| Luminaire efficacy | 130 lm/W @ 4000 K |
| LED service life | 55 000 h (L85) |
| Mains voltage | 220-240V, 50Hz |
| Stand-by consumption | < 0.5 W |
| Safety class | I |
| Protection type | IP 20 |
| Packaging units | 2 (ca. 600 x 600 x 230 + 780/1280 x 200 x 50 mm) |
| Weight | 8.4 kg |
| Guarantee | 36 months |

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com



MINERGIE®

