



| Type/Order No | UPD32-13-8030-WD |
|--|---|
| Lamp type/assembly | Pendant light |
| Version | With adjustable reflectors |
| Colour | Black |
| Colour temperature | 3000 K |
| Colour rendering index | CRI > 80 |
| Operating mode | Wireless Dim |
| Operation | On site |
| Ballast (number) | LED driver (1), cable integrated |
| Length | 1560 mm |
| Reflector | Aluminium, anodised, matte finish / inside in light gold |
| Suspension (number of suspension points) | max. 2000 mm (2) |
| Electronics housing | Aluminium, anodised, matte finish |
| Ceiling rose | White, Ø 108 mm |
| Power cable | Black, 3x0.75mm ² , L 2000 mm |
| Light distribution | Direct / indirect |
| Power consumption | 42 W |
| Mains voltage | 220-240V / 50Hz |
| Stand-by consumption | < 0.5 W |
| Safety class | I |
| Protection type | IP 20 |
| Packaging units | 1 (1750 x 150 x 150 mm) |
| Weight | 4,5 kg |
| Guarantee | 36 months |

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

