



<b>Type</b>	<b>TWI360-13-DTW-WD</b>
Order No	TWI360-13-DTW-WD
Lamp type/assembly	Standing luminaire
Colour	Aluminium, anodised
Energy efficiency class	D
Light source	LED, CRI > 80
Colour temperature	3000K-1800K
Colour rendering index	CRI > 80 Ra
Chromaticity tolerance (initial MacAdam)	3 SDCM
Operating mode	Dimmable
Operation	Dim To Warm / Wireless Dim
Lamp housing	Transparent
Power cable	Black, 3 x 0.75 mm <sup>2</sup> , L 3m
Mains plug	UK plug type G
Light distribution	Direct / indirect
Total luminous flux of luminaire	7810 lm
Power consumption	69 W
Luminaire efficacy	113 lm/W
LED service life	55'000h (L90/F10)
Mains voltage	220-240V / 50Hz
Stand-by consumption	0 W
Protection type	IP 20
Packaging units	1
Weight	9 kg
Tooltip Description	With two dimmers for direct, brilliant mood lighting and indirect room lighting
Guarantee	36 months

**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com

