



belux twilight sophisticatedly combines brilliant room and mood lighting and has been considered a classic floor-standing lamp for over 15 years. The range now features a cylindrical version, which broadens the lamp's range of potential applications in architectural spaces.

belux twilight 360 is available in aluminium and bronze anodized finish. The inner workings of the light fixture feature LED light sources at the top and the bottom, which emit light towards each other and hence produce the belux twilight's characteristic effect. The indirect, high-performance of indirect room lighting. Both light sources can be dimmed independently, enabling endless lighting moods.

Belux AG

www.belux.com

belux@belux.com

Type	TWI360-22-DTW-DD
Order No	TWI360-22-DTW-DD
Lamp type/assembly	Standing light
Colour	Dark Bronze eloxiert
Energy efficiency class	A+
Light source	LED, CRI > 80
Colour temperature	3000K-1800K
Colour rendering index	CRI > 80 Ra
Chromaticity tolerance (initial MacAdam)	3 SDCM
Operating mode	Dimmable
Operation	Dim To Warm, DALI dimmable - on site
Lamp housing	Transparent
Power cable	Black, 3 x 0.75 mm ² , L 3m
Mains plug	without
Light distribution	Direct / indirect
Total luminous flux of luminaire	7120 lm
Power consumption	65 W
Luminaire efficacy	109 lm/W
LED service life	55'000h (L90/F10)
Mains voltage	220-240V / 50Hz
Stand-by consumption	0 W
Protection type	IP 20
Packaging units	1
Weight	9 kg
Guarantee	36 months

