



Type	TWI360-24-8027-TD
Order No	TWI360-24-8027-TD
Lamp type/assembly	Standing luminaire
Colour	Black
Energy efficiency class	D
Light source	LED, CRI > 80
Colour temperature	2700K
Colour rendering index	CRI > 80 Ra
Chromaticity tolerance (initial MacAdam)	3 SDCM
Operating mode	Dimmable
Operation	Touch dim, cable integrated
Lamp housing	Black coloured, semi-transparent
Power cable	Black, 3 x 0.75 mm ² , L 3m
Mains plug	CH T12 (Typ J)
Light distribution	Direct / indirect
Total luminous flux of luminaire	7810 lm
Power consumption	69 W
Luminaire efficacy	113 lm/W
LED service life	55'000h (L90/F10)
Mains voltage	220-240V / 50Hz
Stand-by consumption	0 W
Protection type	IP 20
Packaging units	1
Weight	9 kg
Tooltip Description	With two dimmers for direct, brilliant mood lighting and indirect room lighting
Guarantee	36 months
Belux Express	Small quantities normally available from stock

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

