



Type	DIS10-12-8030-TD
Order No	DIS10-12-8030-TD
Lamp type/assembly	Standing luminaire
Colour	Black
Energy efficiency class	E
Colour temperature	3000K
Colour rendering index	CRI>80
Operating mode	Dimmable
Operation	On lamp head
Lamp head	Aluminium die-cast
Diffuser	PMMA lens
Tube	Steel, black, powder-coated
Base	Round base, steel, black, powder-coated
Power cable	Transparent, 3x0.75mm ² , L 3000 mm
Mains plug	Swiss plug type J
Light distribution	Direct (26.8%) / indirect (73.2%)
Total luminous flux	8590lm
Power consumption	72W
Luminaire efficacy	120 lm/W
LED service life	50'000h
Mains voltage	220-240V, 50/60Hz
Stand-by consumption	< 0.5W
Safety class	I
Protection type	IP 20
Packaging units	2 (480 x 480 x 140 mm + 1920 x 100 x 100 mm)
Weight	12.7 kg
Guarantee	36 months

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

MINERGIE®

light of
the future



γ=80.06% CD/1000lm