



| | |
|----------------------------------|---|
| Type | KID12-15-8030-TD |
| Order No | KID12-15-8030-TD |
| Lamp type/assembly | Standing luminaire |
| Colour | White |
| Light source | LED |
| Energy efficiency class | LED |
| Colour temperature | 3000K |
| Colour rendering index | CRI > 80 |
| Operating mode | Dimmable |
| Operation | On tube |
| Base | U-base |
| Power cable | Black, 3x0.75mm ² , L 3000 mm |
| Mains plug | Schuko plug type E+F |
| Light distribution | Direct (20%) / indirect (80%) |
| UGR | < 11 |
| Total luminous flux of luminaire | 11200lm @ 4000K |
| Power consumption | 90W |
| Luminaire efficacy | 125lm/W @ 4000K |
| Safety class | I |
| Protection type | IP20 |
| Packaging units | 3 (ca. 940 x 380 x 85 + 2000 x 190 x 55 + 570 x 475 x 45 mm) |
| Weight | 16kg |
| Tooltip Description | New workspace lighting |
| Guarantee | 36 months |

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

