



belux kido is a versatile lighting family with a powerful and extremely homogeneous lighting for workplaces. Thanks to the symmetrical or asymmetrical light output belux kido standing light, table light or suspension can be applied for 1, 2 or 4 workplaces and numerous other applications. belux kido is a powerful luminaire of 11200 Lumen yet with only 90W for two workplaces. The direct and indirect light output can be separately switched and dimmed. belux kido is available in black or white.

Belux AG

www.belux.com
belux@belux.com



Type	KID50-15-8030-TD
Order No	KID50-15-8030-TD
Lamp type/assembly	Standing light
Version	Doppelkopf, asymmetrisch.
Colour	White
Light source	LED
Energy efficiency class	LED
Colour temperature	3000K
Colour rendering index	CRI > 80
Operating mode	Dimmable
Operation	On tube
Base	H-base
Power cable	Black, 3x0.75mm ² , L 3000 mm
Mains plug	Schuko plug type E+F
Light distribution	Direct (20%) / indirect (80%)
UGR	< 11
Total luminous flux of luminaire	2 x 11200lm @ 4000K
Power consumption	2x90W
Luminaire efficacy	125lm/W @ 4000K
Safety class	I
Protection type	IP20
Packaging units	3
Weight	30kg
Guarantee	36 months

