



| | |
|----------------------------------|---|
| Type | OTO10-15-9030-TD |
| Order No | OTO10-15-9030-TD |
| Lamp type/assembly | Standing luminaire |
| Colour | White, structured, matt |
| Size | Ø 450 |
| Material | Silicone, steel, aluminium, PMMA |
| Light source | LED |
| Colour temperature | 3000K |
| Colour rendering index | CRI > 90 |
| Operating mode | Dimmable TD |
| Operation | Ambient, direct and indirect light controlled simultaneously |
| Power cable | Black, 3x0.75mm ² , L 3000 mm |
| Mains plug | Schuko plug type E+F |
| Light distribution | Direct (27%) / indirect (73%) |
| UGR | UGR<15 |
| Total luminous flux of luminaire | 11050lm @ 4000K |
| Power consumption | 73W |
| Luminaire efficacy | 151 lm/W @ 4000 K |
| Safety class | I |
| Protection type | IP20 |
| Packaging units | 3 (2050 x 200 x 50mm + 460 x 460 x 40mm + 500 x 500 x 160mm) |
| Weight | 31.14 kg |
| Guarantee | 36 months |

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

