



|                                  |   |
|----------------------------------|---|
| <b>Type</b>                      | <b>OTO10-18-9030-TD</b>   |
| Order No                         | OTO10-18-9030-TD  |
| Lamp type/assembly               | Standing luminaire  |
| Colour                           | Black, structured, matt   |
| Size                             | Ø 450   |
| Material                         | Silicone, steel, aluminium, PMMA                                |
| Light source                     | LED   |
| Colour temperature               | 3000K   |
| Colour rendering index           | CRI > 90  |
| Operating mode                   | Dimmable TD   |
| Operation                        | Ambient, direct and indirect light<br>controlled simultaneously |
| Power cable                      | Black, 3x0.75mm <sup>2</sup> , L 3000 mm                        |
| Mains plug                       | Schuko plug type E+F  |
| Light distribution               | Direct (27%) / indirect (73%)                                   |
| UGR                              | UGR<15  |
| Total luminous flux of luminaire | 11050lm @ 4000K   |
| Power consumption                | 73W   |
| Luminaire efficacy               | 151 lm/W @ 4000 K   |
| Safety class                     | I   |
| Protection type                  | IP20  |
| Packaging units                  | 3 (2050 x 200 x 50mm + 460 x 460 x<br>40mm + 500 x 500 x 160mm) |
| Weight                           | 31.14 kg  |
| Guarantee                        | 36 months   |



**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com

