



<b>Type</b>	<b>OTO46-15-9030-MS</b>
Order No	OTO46-15-9030-MS
Lamp type/assembly	Desk-mounted luminaire
Version	Universal-D
Cable exit	Underneath the tabletop
Colour	White, structured, matt
Size	Ø 450
Material	Silicone, steel, aluminium, PMMA
Light source	LED
Colour temperature	3000K
Colour rendering index	CRI > 90
Operating mode	Multisens
Operation	On tube
Lamp head	Silicone, aluminium, PC
Diffuser	Silicone (UV-proof) + prismatic PC
Tube	Steel, black, structured, matt
Power cable	Black, 3x0.75mm <sup>2</sup> , L 3000 mm
Mains plug	Schuko plug type E+F
Light distribution	Direct 27% / Indirect 73%
UGR	UGR<15
Total luminous flux of luminaire	11050lm @ 4000K
Power consumption	73W
Luminaire efficacy	151lm/W
Mains voltage	220-240V, 50Hz
Stand-by consumption	<0,5W
Safety class	I
Protection type	IP20
Packaging units	2 (1350 x 500 x 50mm + 500 x 500mm)
Weight	8.7 kg
Guarantee	36 months

**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com



reddot winner 2025  
lighting design

