



Type	KRO10-11-8040-DD
Order No	KRO10-11-8040-DD
Lamp type/assembly	Standing light
Version	Symmetrical light distribution
Colour	Black
Light source	LED, 4000 K, 5900 lm, CRI > 80
Operating mode	Dimmable DALI
Operation	On site
Ballast (number)	Driver (1), integrated integrated in lamp base
Lamp head	Aluminium, die-cast
Diffuser	PMMA
Tube	Aluminium, extruded
Base	Zamak
Finish	Black RAL 9005, powder-coated
Power cable	Black, 5x0.75mm ² , L 3000 mm
Mains plug	CH (type J), Schuko (type F) or UK (type G)
Light distribution	Direct (44%) / indirect (56%)
UGR	< 12
Power consumption	93 W
Luminaire efficacy	100%
Mains voltage	220-240V, 50/60Hz
Stand-by consumption	< 0.5 W
Safety class	I
Protection type	IP 20
Packaging units	1 (1960 x 600 x 600 mm)
Weight	16 kg
Guarantee	36 months

KRO10-11-8040-DD



Belux AG

Neufeldweg 6, CH-5103 Möriken
 Tel. +41 61 316 74 01
 Fax +41 61 316 75 99
 www.belux.com
 belux@belux.com