



Type	OTO43-12-9030-MS
Order No	OTO43-12-9030-MS
Lamp type/assembly	Desk-mounted luminaire
Version	USM Haller
Cable exit	Lateral
Colour	Chrome
Size	Ø 450
Material	Silicone, steel, aluminium, PMMA
Light source	LED
Colour temperature	3000K
Colour rendering index	CRI > 90
Operating mode	Multisens
Operation	Self-adjusting
Lamp head	Silicone, aluminium, PC
Diffuser	Silicone (UV-proof) + prismatic PC
Tube	Chrome
Power cable	Black, 3x0.75mm ² , L 3000 mm
Mains plug	Schuko plug type E+F
Light distribution	Direct 27% / Indirect 73%
UGR	UGR<15
Total luminous flux of luminaire	11050lm @ 4000K
Power consumption	73W
Luminaire efficacy	151lm/W
Mains voltage	220-240V, 50Hz
Stand-by consumption	<0,5W
Safety class	I
Protection type	IP20
Packaging units	2 (1350 x 500 x 50mm + 500 x 500mm)
Weight	8.7 kg
Remark	Not compatible with height adjustable tables
Guarantee	36 months

Belux AG

Neufeldweg 6, CH-5103
Möriken
Tel. +41 61 316 74 01
Fax +41 61 316 75 99
www.belux.com
belux@belux.com

